

Coolio® Connect



- ✓ Easy to move
- ✓ Multi-product cool display
- ✓ Various branding possibilities
- ✓ Maximum product visibility



External dimensions

W 775mm
D 850mm
H 1120mm



Gross weight

85kg



Refrigerant

R290 - 150 gr



Range Cool

-1°C to +5°C



Range Freeze

-18°C to -15°C

Coolio® Connect



Main features

- ✓ 1 cooler, 2 solutions: cool & freeze
- ✓ Easy access
- ✓ Robust, high-end design
- ✓ Easy to brand and rebrand
- ✓ Green refrigerant R290
- ✓ Easy maintenance
- ✓ Electronic thermostat with automatic defrosting

Technical details

Net Weight (kg)	85
TDA (Total Display Area) [m2]	0,86
Net volume (l)	120
External dimensions W x D x H (mm)	775 x 850 x 1120
Internal dimensions W x D x H (mm)	630 x 620 x 300
Operating Voltage Range	220-240V, 50Hz
Defrosting	Hot Gas
Lighting	LED
Refrigerant	R290 - 150 gr
Energy consumption Cool Function (kWh/24h)	4,4
Energy consumption Freeze Function (kWh/24h)	8,5
Temperature control	Electronical
EU Energy Label	E
Power Cable	Spiral cable 5m, type E plug

Temperatures

Temperature Range Cool Function	-1°C to +5°C
Temperature Class Cool Function	3M1
Temperature Range Freeze Function	-18°C to -15°C
Temperature Class Freeze Function	3L1
Climate class	3 (25°C, 60% relative humidity)

Transportation

Gross weight (kg)	100
Package size W x D x H (mm)	800 x 880 x 1300
Quantity 20ft container (pcs)	30
Quantity 40ft container (pcs)	14
Quantity 13,6m truck (pcs)	34

Coolio® Connect

Shelf Dimensions

Bottom Plate W x D (mm)

630 x 620

Variants

Options

Divider with 4 compartments

Power cable type G (UK) , type J (CH) or
CEE-plug | standard type E